

**AMENDMENTS TO THE CLAIMS WITH MARKINGS TO SHOW CHANGES  
MADE, AND LISTING OF ALL CLAIMS WITH PROPER IDENTIFIERS**

1. (Currently amended) A method for controlling an electrical machine ~~[[5]]~~  
for modifying a position of a movable machine part, comprising the steps of:  
detecting a position of the movable machine part; and  
varying at least one parameter of at least one member of with a control  
unit ~~[[1] having]]~~ selected from the group consisting of a configurable speed  
regulator ~~(26) and/or~~ and a configurable additional regulator ~~(28) and the~~  
~~electrical machine (5) being provided in order to vary a position of a~~  
~~movable machine part (7, 8), with the position (29) of the movable machine~~  
~~part (7, 8) being detected, characterized in that at least one parameter (31)~~  
~~of the speed regulator (26) and/or at least one parameter (33) of the~~  
~~additional regulator (28) are/is varied as a function of the position [[(29)]] of~~  
~~the movable machine part [[(7, 8)]]~~.
2. (Currently amended) The method as claimed in claim 1, ~~characterized in~~  
~~that wherein the additional regulator is~~ at least one of the following regulator  
~~types is used as the additional regulator (28):~~ selected from the group  
consisting of position regulator, traction regulator, torque regulator, and pilot  
control.
3. (Currently amended) The method as claimed in claim 1 ~~[[or 2]]~~,  
~~characterized in that wherein the electrical machine is~~ a linear motor ~~(5) is~~  
~~used as the electrical machine (5), with the linear motor (5) having a primary~~  
~~part [[(7)]] and a secondary part [[(8)]]~~, with either the primary part ~~[[(7)]]~~ or  
the secondary part ~~[[8) being a]]~~ representing the movable machine part of  
the linear motor ~~(5), and at least one parameter (31) of the speed regulator~~  
~~(26) and/or at least one parameter (33) of the additional regulator (28) being~~  
~~varied as a function of the position of the movable machine part.~~

4. (Currently amended) The method as claimed in ~~one of claims 1 to 3~~ claim 1, ~~characterized in that~~ wherein the varying step includes the step of using a function [(35)] or a table (37) is used in order to vary the parameter (31, 33).
5. (Currently amended) The method as claimed in ~~one of claims 1 to 4~~, claim 1 ~~characterized in that~~ wherein the detecting step includes the step of executing a reference run of the electrical machine (5) is carried out in order to determine the parameters (31, 33) parameter which are is dependent on the position of the movable machine part.
6. (Currently amended) The method as claimed in ~~one of claims 1 to 5~~ claim 1, ~~characterized in that~~ further comprising the step of measuring one physical parameter which in particular is a magnetic field parameter is measured as a function of the position [(29)] of the machine parts [(7, 8)], and the parameter [(31, 33)] of a regulator the member is varied as a function of the position [(29)] of the machine part [(7, 8)] and as a function of the physical parameter.
7. (Currently amended) An apparatus for controlling an electrical machine [(5)] for modifying a position of a movable machine part, [with the] comprising a control system having a configurable speed regulator [(26)] and a configurable additional regulator [(28)], and the electrical machine (5) being provided in order to vary the position of the machine part (7, 8), with the position of the machine part [(7, 8)] being measurable, characterized in that wherein at least one parameter [(31)] of the speed regulator [(26)] and/or at least one parameter [(33)] of the additional regulator [(28) can be varied] is variable as a function of the position [(29)] of the machine part [(7, 8)].

8. (Currently amended) The apparatus as claimed in claim ~~[[6]]~~ 7,  
~~characterized in that this apparatus is intended to carry~~ for carrying out the  
method as claimed in ~~one of claims 1 to 6~~ claim 1.
9. (New) The method of claim 6, wherein the physical parameter is a magnetic  
field parameter.